



DECLARATION OF PERFORMANCE

Nº. A001CPR2013-06-22

1. Unique code of identification for each type of product:
Dry-pressed ceramic tiles, with water absorption $H_2O E \leq 0,5\%$
2. Destination of use:
Internal and external walls and floorings
3. Name or trade mark and address of manufacturer:
**CIPA GRES S.p.A.
Via Statale 467, 119 - 42013 Casalgrande (RE) - Italia**
4. System of assessment and verification of constancy of performance (AVCP):
System 4
5. Name and number of identification of laboratory notified, if applicable: **Not Applicable**
6. Declared performance:

Essential characteristics	Performance	Harmonized technical Specification
Fire Resistance	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substances, for:		
▪ Cadmium	npd	
▪ Lead	npd	
Breaking Strength	Thickness < 7,5mm Breaking strength ≥ 700 N	
	Thickness ≥ 7,5mm Breaking strength ≥1300 N	
Tactility	npd	
Slip Resistance	See Table attached	
Bond Strength for:		
▪ Adhesion cement, Type C2	npd	
Resistance to thermal shocks	Resistant	
Durability for:		
▪ Internal use	Resistant	
▪ External use: frost resistance	Resistant	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) N.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Casalgrande, 06/11/2025

Giovanni Fiandri
Chief Executive Officer
CIPA GRES SPA
Via Statale 467 n. 119
42013 CASALGRANDE (RE) ITALY
Tel. +39 0522 846890 Fax +39 0522 849910
Partita IVA IT 01409620356
Codice Fiscale 01880740368

EN-REV.N.5



ATTACHMENT TO DECLARATION OF PERFORMANCE

Nº. A001CPR2013-06-22

TABLE - SLIPPERINESS

Rev.5 of 06/11/2025

Series	CEN/TS 16165	BCRA D.M. 236/1989 (IT)	DIN EN 16165 Annex B (DE)	UNE EN 16165 Annex C (ES)
HI-TECH GRANITI Natural	npd	npd	R9	CLASS 1
HI-TECH GRANITI Roccia	npd	>0,4	R11	CLASS 3
HI-TECH GRANITI R10	npd	npd	R10	CLASS 2
HI-TECH GRANITI SLR	npd	>0,4	R11	CLASS 3
HI-TECH GRANITI Quadri	npd	>0,4	R11	CLASS 3
HI-TECH GRANITI Line	npd	>0,4	R12	CLASS 3
HI-TECH GRANITI Star	npd	>0,4	R12	CLASS 3
HI-TECH GRANITI Point	npd	>0,4	R12	CLASS 3
HI-TECH GRANITI Rustico	npd	>0,4	R11	CLASS 3
HI-TECH GRANITI Polished	npd	npd	npd	CLASS 0
HI-TECH Square	npd	>0,4	R12	npd
HI-TECH Corindo	npd	>0,4	R13	CLASS 3
HI-TECH Carborundum	npd	>0,4	R12	npd
HI-TECH Pave'	npd	>0,4	R12	npd
HI-TECH Aste	npd	>0,4	R12	npd
HI-TECH CCv Grip	npd	>0,4	R13	CLASS 3
HI-TECH GRANITI CONTRACT Nat.	npd	npd	R9	CLASS 1
HI-TECH GRANITI CONTRACT Roccia	npd	>0,4	R11	CLASS 3
HI-TECH GRANITI CONTRACT R10	npd	npd	R10	CLASS 2
HI-TECH GRANITI CONTRACT SLR	npd	>0,4	R11	CLASS 3
HI-TECH NODOTS Natural	npd	npd	R9	CLASS 1
HI-TECH NODOTS R10	npd	>0,4	R10	CLASSE 2
HI-TECH NODOTS SLR	npd	>0,4	R11	CLASSE 3
HI-TECH GRANATI Natural	npd	npd	R9	CLASS 1
HI-TECH GRANATI Roccia	npd	>0,4	R11	CLASS 3
HI-TECH GRANATI Polished	npd	npd	npd	CLASS 0
HI-TECH COLOURSTYLE Natural	npd	npd	R9	CLASS 1
HI-TECH COLOURSTYLE R10	npd	npd	R10	CLASS 2
HI-TECH COLOURSTYLE Roccia	npd	>0,4	R11	CLASS 3
HI-TECH COLOURSTYLE SLR	npd	>0,4	R11	CLASS 3
HI-TECH COLOURSTYLE Star	npd	>0,4	R12	CLASS 3
HI-TECH COLOURSTYLE Line	npd	>0,4	R12	CLASS 3
HI-TECH COLOURSTYLE Rustico	npd	>0,4	R11	CLASS 3
HI-TECH COLOURSTYLE Polished	npd	npd	npd	CLASS 0
LOGES	npd	npd	npd	npd
PORFIDO	npd	npd	R11	npd
BORGHESI MEDIEVALI	npd	npd	R11	npd
PIETRE	npd	>0,4	R11	npd
MARMO ANTICO	npd	>0,4	R10	npd

EN-REV.N.5



CE MARKING

Full Body Porcelain Tile

	
CIPA GRES S.p.A. Via Statale 467, 119 - 42013 Casalgrande (RE) - Italia 05 No. A001CPR2013-06-22	
EN 14411:2012 Dry pressed ceramic tiles, with water absorption $E \leq 0,5$ % for floors and internal /external walls	
Fire Resistance	A1 _{FL} /A1
Release of dangerous substances, for:	
▪ Cadmium	npd
▪ Lead	npd
Breaking Strength	Thickness < 7,5mm Breaking Strength ≥ 700 N
	Thickness $\geq 7,5$ mm Breaking Strength ≥ 1300 N
Tactility	npd
Slip resistance	See Table attached
Bond Strength for:	
▪ Adhesion Cement, Type C2	npd
Resistance to thermal shocks	Resistant
Durability for:	
▪ Internal Use	Resistant
▪ External Use: frost resistance	Resistant

EN-REV. N. 5