



In-depth cleaning **CEMENT/O PROREMOVER**

Product for in-depth cleaning and refurbishing

Cement/o Proremover is designed for the in-depth cleaning of hard surfaces such as ceramics, porcelain stoneware, granite, concrete, etc.

The product is applied using a low pressure spray and agitated on the surface to remove limescale, grease marks, stubborn dirt and most of the indoor and outdoor surface contamination caused by pedestrian traffic.

Cement/o Proremover is used to remove limescale and restore and refurbish the original texture and appearance of hard and rubber surfaces without altering the substrate or damaging the cementitious material or fixing agents.



**PRIVATE
CLEANING STAFF**



**PROFESSIONAL USE
CIPA INDUSTRIAL SERVICE**



- ▶ In-depth cleaning and refurbishing treatment for floors and walls
- ▶ Cleaning after laying
- ▶ Complete refurbishment of surfaces to restore the original appearance
- ▶ Remove stains patinas created by soap
- ▶ Perfect for glazed, structured or polished stoneware
- ▶ Effective on all indoor or outdoor surfaces
 - industrial: ceramics, concrete
 - natural: marble, granite, stone
 - building cladding: aluminum, plastic, concrete
- ▶ Specialized treatment to resolve a variety of problems associated with the deterioration of materials and poor hygiene:
 - limescale (bathrooms, kitchens, swimming pools)
 - chemical, organic and industrial stains
 - refurbishment of external facade

USE ON:

CERAMICS glazed stoneware,
structured and polished
CONCRETE
MARBLE not polished
GRANITE
STONE
GLASS with lime

NOT USE ON:

MARBLE and acid-sensitive
materials
WOOD
METALS
POLISHED LAPPED GRES




In-depth cleaning CEMENT/O PROREMOVER

CONDITIONS OF USE


Always try on areas not too highlighted before you begin treatment.
For best results, apply **Cement/o Proremover** to a dry surface.
Use undiluted to remove limescale and refurbish vitrified stoneware surfaces.




1 Dilute the product according to the treatment required



2 Apply to the surface with mop in ultra microfiber




For walls, spray or apply with a sponge




3 Leave to work for 5-15 minutes

YOU ARE RECOMMENDED TO TREAT 20/30mq AT A TIME



4 Rub the surface with a microfiber mop and green pad or a washer-dryer



5 Rinse with one liter of water for every 20/30 mq



6 Collect the solution with mop in ultra microfiber or machine aspiraliquide



7 Dry the surface using the mop and the dry microfiber cloth

REPEAT UNTIL THE DESIRED EFFECT IS ACHIEVED

EFFECTIVE AGAINST STAINS ► RUST ► CONCRETE ► LIMESTONE ► BITUMEN ► DIRTY ESCAPE ► METAL SIGNS

TECHNICAL SPECIFICATIONS

APPEARANCE	opaque liquid
FRAGRANCE	not intense
SPECIFIC WEIGHT	-
BOILING POINT	100°C
PACK	5 litre containers
PH	2.1 ~ when diluted pH 4.0 ~
VOLATILE ORGANISMS- VOC	-
BIODEGRABILITY	100%
MAXIMUM DILUTION	20:1
WATER SOLUBILITY	100%
CHEMICAL COMPOSITION (reg.684/2004)	-
WARNINGS	if necessary, wear personal protection devices

The above information is based on the product data in our possession at the moment of publication and is provided in good faith. No guarantee is provided as regards the quality or specifications of the product. The user is personally responsible for verifying that the product is suitable for the purpose.